

PCT


WORLD INTELLECT  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04B 1/707</b>		(11) International Publication Number: <b>WO 96/04716</b>
A1		(43) International Publication Date: 15 February 1996 (15.02.96)
(21) International Application Number: PCT/US95/08659 (22) International Filing Date: 10 July 1995 (10.07.95) (30) Priority Data: 283,304 29 July 1994 (29.07.94) US (71) Applicant: QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US). (72) Inventor: SUTTON, Todd, R.; 11275 Caminito Rodar, San Diego, CA 92126 (US). (74) Agent: MILLER, Russell, B.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).  Published With international search report.

(54) Title: METHOD AND APPARATUS FOR PERFORMING CODE ACQUISITION IN A CDMA COMMUNICATIONS SYSTEM



(57) Abstract

A novel and improved method of acquisition in a spread spectrum communication system is presented. In the present invention, a large window of PN chip offset hypotheses are searched which are generated by a PN sequence generator (20) under the control of a searcher controller (18). The energy of the despread sequence which is despread by a despreader (6) is found that might indicate the presence of the pilot signal in a threshold comparer (16) having one of the chip offsets of the large search window, then a search of a subset of offset hypotheses, or small window, is searched under the control of searcher controller (18).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Method and Apparatus for Performing Code Acquisition in a  
CDMA Communications System

5                                   **BACKGROUND OF THE INVENTION**

**I. Field of the Invention**

The present invention relates to spread spectrum communications.  
10 More particularly, the present invention relates to a novel and improved  
method and apparatus for acquisition in spread spectrum communication  
environment.

15                                   **II. Description of the Related Art**

The use of code division multiple access (CDMA) modulation  
techniques is one of several techniques for facilitating communications in  
which a large number of system users are present. Other multiple access  
communication system techniques, such as time division multiple access  
20 (TDMA) and frequency division multiple access (FDMA) are known in the  
art. However, the spread spectrum modulation technique of CDMA has  
significant advantages over these modulation techniques for multiple access  
communication systems. The use of CDMA techniques in a multiple access  
communication system is disclosed in U.S. Patent No. 4,901,307, issued  
25 February 13, 1990, entitled "SPREAD SPECTRUM MULTIPLE ACCESS  
COMMUNICATION SYSTEM USING SATELLITE OR TERRESTRIAL  
REPEATERS", assigned to the assignee of the present invention, of which  
the disclosure thereof is incorporated by reference herein.

CDMA by its inherent nature of being a wideband signal offers a form  
30 of frequency diversity by spreading the signal energy over a wide bandwidth.  
Therefore, frequency selective fading affects only a small part of the CDMA  
signal bandwidth.

Space or path diversity is obtained by providing multiple signal paths  
through simultaneous links from a mobile user through two or more cell-  
35 sites. Furthermore, path diversity may be obtained by exploiting the  
multipath environment through spread spectrum processing by allowing a  
signal arriving with different propagation delays to be received and  
processed separately. Examples of the utilization of path diversity are  
illustrated in U.S. Patent No. 5,101,501, issued March 31, 1992, entitled  
40 "SOFT HANDOFF IN A CDMA CELLULAR TELEPHONE SYSTEM", and

U.S. Patent No. 5,109,390, issued April 28, 1992, entitled "DIVERSITY RECEIVER IN A CDMA CELLULAR TELEPHONE SYSTEM", both assigned to the assignee of the present invention and incorporated by reference herein.

5       The deleterious effects of fading can be further controlled to a certain extent in a CDMA system by controlling transmitter power. A system for cell-site and mobile unit power control is disclosed in U.S. Patent No. 5,056,109, issued October 8, 1991, entitled "METHOD AND APPARATUS FOR CONTROLLING TRANSMISSION POWER IN A CDMA CELLULAR  
10 MOBILE TELEPHONE SYSTEM", Serial No. 07/433,031, filed November 7, 1989, also assigned to the assignee of the present invention. The use of CDMA techniques in a multiple access communication system is further disclosed in U.S. Patent No. 5,103,459, issued April 7, 1992, entitled "SYSTEM AND METHOD FOR GENERATING SIGNAL WAVEFORMS IN A CDMA  
15 CELLULAR TELEPHONE SYSTEM", assigned to the assignee of the present invention, of which the disclosure thereof is incorporated by reference herein.

      The aforementioned patents all describe the use of a pilot signal used for acquisition. The use of a pilot signal enables the mobile station to  
20 acquire local base station communication system in a timely manner. The mobile station gets synchronization information and relative signal power information from the received pilot signal.

      In an ideal system where the hardware set up time is zero, a search window of one hypothesis would be ideal. However, because it takes time  
25 to set up the hardware to conduct searches windows of hypotheses are tested. The longer the time required to set up the hardware, the larger the necessary window size. In complex systems a searcher is required to search a window of many hypotheses and upon finding a candidate synchronized sequence, will repeat the search over the window a predetermined number  
30 of times to verify the synchronization. This process requires an unacceptably long acquisition time. The present invention provides a method and apparatus for accelerating the time required to acquire a the pilot signal in a mobile communications system.

35

## SUMMARY OF THE INVENTION

      The present invention is a novel and improved method and apparatus that reduces the mobile unit forward link acquisition time. It is an advantage of the present invention to minimize the total time for

acquisition by speeding up the search methodology without incurring excessive penalties for false acquisition.

5 A method for determining and verifying the phase of a pilot channel in a spread spectrum communication system comprising the steps of determining a set of calculated energy values for a first predetermined large window set of PN sequence hypotheses; comparing the set of calculated energy values against a first threshold value; determining a second set of calculated energy values for a predetermined small window set of PN sequence hypotheses wherein the small window PN sequence hypotheses are a subset of the large window set of PN sequence hypotheses when at least one energy value of the set of calculated energy values exceeds the first threshold value; and determining the phase of the pilot channel in accordance with the second set of calculated energy values.

## 15 BRIEF DESCRIPTION OF THE DRAWINGS

The features, objects, and advantages of the present invention will become more apparent from the detailed description set forth below when taken in conjunction with the drawings in which like reference characters identify correspondingly throughout and wherein:

Figure 1 is a block diagram of the present invention;

Figure 2 is an illustration of the energy versus chip offset for a fixed window;

Figure 3 is a flowchart illustrating a fixed window size implementation of the searcher algorithm;

Figure 4 is an illustration of the energy versus chip offset for the zoom window of the present invention; and

Figure 5 is an illustration of the energy versus chip offset for the zoom window implementation of the present invention.

## 30 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In a spread spectrum communication system, a pilot signal is used to synchronize a mobile station in phase and frequency to the transmissions of a base station. In the exemplary embodiment, the spread spectrum communication system is a direct-sequence spread spectrum communication system. Examples of such systems are discussed in U.S. Patent No. 5,056,109 and U.S. Patent No. 5,103,459. In a direct-sequence

spread spectrum communication system, the transmitted signals are spread over a frequency band greater than the minimum bandwidth necessary to transmit the information by modulating a carrier wave by the data signal, then modulating the resulting signal again with a wideband spreading  
5 signal. In a pilot signal, the data can be looked at as an all ones sequence.

The spreading signal is typically generated by a linear feedback shift register, the implementation of which is described in detail in the aforementioned patents. The spreading signal can be viewed as a rotating phasor of the form:

10

$$s(t) = Ae^{-\omega t + \phi}$$

(1)

In order to acquire, the mobile station must synchronize to the  
15 received signals from the base station in both phase,  $\phi$ , and in frequency,  $\omega$ . The object of the searcher operation is to find the phase of the received signal,  $\phi$ . After finding the phase of the spreading signal,  $\phi$ , the frequency is found in using a demodulation element that has hardware for both phase and frequency tracking. The method by which a mobile finds the phase of  
20 the received signal is by testing a set of phase hypotheses, referred to as a window and determining if one of the hypothetical phase hypotheses, also referred to as offset hypotheses, is correct.

Turning now to the drawings, Figure 1 illustrates the apparatus of the present invention. Upon power up, a spread spectrum signal is received at  
25 antenna 2. The objective of the apparatus is to gain synchronization between pseudorandom noise (PN) sequences generated by PN sequence generator 20 and the received spread spectrum signal which is spread by identical PN sequences of unknown phase.

In the exemplary embodiment, both the modulator that spreads the  
30 pilot signal and PN generator 20 are a maximal length shift register which generate the PN code sequences for spreading and despreading the pilot signal respectively. Thus, the operation of obtaining synchronization between the codes used to despread the received pilot signal and the PN spreading code of the received pilot signal involves determining the time  
35 offset of the shift register.

The spread spectrum signal is provided by antenna 2 to receiver 4. Receiver 4 downconverts the signal and provides the signal to despreading element 6. Despreading element 6 multiplies the received signal by the PN code generated by PN generator 20. Due to the random noise like nature of

the PN codes the product of the PN code and the received signal should be essentially zero except at the point of synchronization.

However, due to a lack of synchronization on a chip level and due to introduced noise this is not the case, which gives rise to false alarm situations where the mobile station may believe that it has successfully acquired the pilot signal but in reality it has not. In order to give higher certainty to the determined condition of successful lock, the test is repeated a number of times. The number of times the test is repeated is determined by searcher controller 18. Searcher controller 18 may be implemented in hardware using a microprocessor or micro-controller or alternatively in software.

Searcher controller 18 provides an offset hypothesis to PN generator 20. In the exemplary embodiment, the received signal is modulated by quadrature phase shift keying (QPSK), so PN generator provides a PN sequence for the I modulation component and a separate sequence for the Q modulation component to despreading element 6. Despreading element 6 multiplies the PN sequence by its corresponding modulation component and provides the two output component products to coherent accumulators 8 and 10.

Coherent accumulators 8 and 10 sum the product over the length of the product sequence. Coherent accumulators 8 and 10 are responsive to signals from searcher controller 18 for resetting, latching and setting the summation period. The sums of the products are provided from summers 8 and 10 to squaring means 14. Squaring means 14 squares each of the sums and adds the squares together.

The sum of the squares is provided by squaring means 12 to non-coherent combiner 14. Noncoherent combiner 14 determines an energy value from the output of squaring means 12. Noncoherent accumulator 14 serves to counteract the effects of a frequency discrepancy between the base station transmit clocks and the mobile station receive clock and aids in the detection statistic in a fading environment. If one knows that the frequency of the two clocks are exactly the same and that there is no deep fades then the ideal approach is to integrate the sequence over the entire accumulation period in the form:

$$E = \left( \sum_{n=1}^N I(n) PNI(n) \right)^2 + \left( \sum_{n=1}^N Q(n) PNQ(n) \right)^2$$

(2)

, where  $PNI(n)$  and  $PNQ(n)$  can be  $\pm 1$ .

If, however, there is a probability of frequency mismatch or fading, then the correlator sacrifices some of its detection statistic in order to have a more robust correlation technique of the form:

$$E = \sum_{k=1}^M \left\{ \left( \sum_{n=1}^N I(n + (k-1)N) \cdot PNI(n + (k-1)N) \right)^2 + \left( \sum_{n=1}^N Q(n + (k-1)N) \cdot PNQ(n + (k-1)N) \right)^2 \right\} \quad (3)$$

10

Searcher controller 18 provides the value  $M$  to noncoherent accumulator 14.

Noncoherent accumulator 14 provides the energy signal to comparison means 16. Comparison means 16 compares the energy value to predetermined thresholds supplied by searcher controller means 18. The results of each of the comparisons is then feedback to searcher controller 18. Search controller 18 examines the comparisons and determines whether the window contains likely candidates for the correct offset then the window is rescanned in accordance with the method of using a zoom window.

In order to illustrate the benefits of using the zoom window technique an example of the method using a fixed window size is provided. Figure 2 illustrates a graph of the energy values versus the chip time hypothesis. In the exemplary embodiment a window contain 56 chip hypotheses. The window illustrates the use of a two level threshold test. The thresholds denoted are detection threshold and validation threshold.

Figure 3 illustrates a conventional method used for scanning windows of a fixed number of hypotheses. The flow starts in block 40, where the operation described in relation to Figure 1 is performed to give comparison results indicated in Figure 2. If the window is "swept" and no hypothesis's energy exceeds the detection threshold (THM) block 42, then searcher controller 18 would begin sweeping the next window blocks 47 and block 40.

However, if there are points on the calculated energy curve which do exceed the detection threshold (THM), then the flow proceeds to the validation phase in block 44. In block 44, the same large window is swept



again, and this time the calculated energy is compared against the lower threshold value, validation threshold (THV). If in block 42 the maximum energy detected does not exceed the threshold, then a next large window is swept in blocks 47 and 40. The flow proceeds to block 48 which determines if validation for twenty consecutive windows has occurred. If fewer than N validation tests, where for example N equals twenty, have been conducted then the flow proceeds to block 44 and the large window is swept again. However, after N consecutive successful validation tests then the pilot is determined to be acquired.

10 Now turning to Figure 4, the calculated energy curve is illustrated and the use of the zoom window of the present invention is illustrated. When a peak is detected, the searcher controller zooms in on that peak and tests hypotheses in a smaller set close to the hypothesis that gave rise to the detected peak.

15 Turning to Figure 5, a flowchart illustrating the method by which the searcher of the present invention operates. In the improved method of the present invention a three stage acquisition technique is used. In block 80, the large window is swept. Searcher controller 18 examines the comparison results to determine if there is a peak greater than Detection Threshold (THM). If no peak is detected greater than THM then the flow returns to block 80 and a new window is swept.

20 When a peak greater than THM is found in a large window, then the flow proceeds to block 84. This time only a sweep in the smaller set of hypotheses around the detected peak is performed. This smaller set of hypotheses is illustrated in Figure 4 as the small window. The use of the small window for the second verification is to reduce the acquisition time by greatly reducing the time to test for false alarm, the state wherein the mobile initially believes it has narrowed in on the phase, but in reality has not. The time it takes to perform this second test is reduced proportionally to the ratio between the number of hypotheses in the small window versus the number of hypotheses in the large window. Noncoherent accumulations are performed in on the data from this small window search in order to have a better operating characteristic.

25 Then in block 86, if there is energy greater than Detection threshold 2 (THM2), the search enters the validation phase. If no energy greater than the threshold THM2 is found then the flow returns to block 80 and a new large window is searched.

30 If in block 86, it is determined that there is a calculated energy value greater than threshold 2 (THM2), then the flow proceeds to block 88. There

are three conditions under which validation is stopped: (1) the sweep fails  $V_f$  in a row, (2) the frequency estimate doubles back on itself from on 100ms sample to the next, or (3) determine that the pilot has been acquired. In validation, the signal at the peak is demodulated. In block 88, the received  
5 signal is demodulated in accordance with the hypothesis of the peak. The results of the demodulated signal are analyzed to determine if they are in lock, and if so then acquisition is complete. If the demodulated results indicate that the signal is not in lock, then the flow proceeds to block 92.

10 In Block 92, the calculated energy values for the small window are compared to the validation threshold value (THV). If in Block 92, there are calculated energy values in the small window which exceed the validation threshold then the flow proceeds to block 94 where a counter variable is set to zero and then the flow proceeds back to block 88 and the flow continues as previously described.

15 If in Block 92, there are no calculated energy values in the small window which exceed the validation threshold then the flow proceeds to block 96 where a counter variable is incremented and then the flow proceeds back to block 98 which checks if the validation test has failed twice in a row. If the validation test has failed  $V_f$  times in a row, then the flow proceeds to  
20 block 80 and a new large window is scanned. If the validation test has not failed twice in a row, then the flow proceeds to block 88 and the operation continues as described previously.

The previous description of the preferred embodiments is provided to enable any person skilled in the art to make or use the present invention.  
25 The various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use of the inventive faculty. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent  
30 with the principles and novel features disclosed herein.

## CLAIMS

1. In a direct sequence spread spectrum communication system, a method for determining PN sequence synchronization, comprising the steps of:
  - calculating a first set of signal correlation energy values for a first set of temporally offset PN sequences;
  - comparing said first set of signal correlation energy values against a first threshold value;
  - selecting a second set of PN sequences in accordance with said first set of signal correlation energy values;
  - calculating a second set of signal correlation energy values for said second set of PN sequences, wherein said second set of PN sequences are a subset of said first set of PN sequences; and
  - selecting said synchronized PN sequence from said second set of PN sequences in accordance with said second set of signal correlation energy values.
2. The method of Claim 1 further comprising the step of comparing said second set of signal correlation energy values against a second threshold value.
3. The method of Claim 2 further comprising the step of demodulating a received signal in accordance with said selected synchronized PN sequence.
5. The method of Claim 1 further comprising the step of receiving and downconverting a broadcast signal to provide a received signal.
6. The method of Claim 5 wherein said step of calculating a first set of signal correlation energy values comprises the steps of:
  - despreading said received signal in accordance with each PN sequence of said first set of PN sequences to provide a first set of despread signals; and
  - calculating a signal correlation energy value for each of said despread signals.
7. The method of Claim 1 further comprising the step of generating said first set of PN sequences.

8. The method of Claim 7 wherein said the step of generating said  
2 first set of PN sequences, comprises the steps of:  
providing a control signal; and  
4 generating a PN sequence of said first set of PN sequences in  
accordance with said control signal.

9. The method of Claim 8 wherein said control signal is a  
2 temporal offset and said step of generating a PN sequence comprises  
outputting said PN sequence from a shift register in accordance with said  
4 temporal offset.

10. The method of Claim 1 wherein said first set of PN sequences  
2 comprise quadrature  $PN_I$  and  $PN_Q$  sequences.

11. The method of Claim 10 wherein said step of calculating said  
2 signal correlation energy value for each of said despread signals comprises  
the steps of:  
4 generating said  $PN_I$  and  $PN_Q$  sequences;  
despreading an I component of a received signal and a Q component  
6 of a received signal by said  $PN_I$  and  $PN_Q$  sequences to provide  
corresponding despread I and Q components of said received signal;  
8 coherently accumulating said despread I components of said received  
signal to provide an accumulated I component;  
10 coherently accumulating said despread Q components of said received  
signal to provide an accumulated Q component;  
12 squaring each of said accumulated I component and said accumulated  
Q component and summing said squares of said accumulated I component  
14 and said accumulated Q component; and  
noncoherently combining said sum of said squares of said  
16 accumulated I component and said accumulated Q component.

12. An apparatus for selecting a synchronized demodulation  
2 sequence comprising:  
sequence generator means for receiving a first control signal for  
4 providing a plurality of demodulation sequences in response to said first  
control signal;

6 demodulator means for receiving a received signal and demodulating  
a received signal in accordance with said plurality of demodulation  
8 sequences to provide a plurality of despread signals;

correlator means for receiving said plurality of despread signals and  
10 calculating signal correlation energy values for said plurality of despread  
signals;

12 searcher controller means for receiving said signal correlation energy  
values and for providing said first control signal and for providing a second  
14 control signal in accordance with said signal correlation energy values; and

wherein said sequence generator means is further for receiving said  
16 second control signal and for providing a second plurality of demodulation  
sequences in response to said second control signal and wherein said second  
18 plurality of demodulation sequences are a subset of said first plurality of  
demodulation sequences.

13. The apparatus of Claim 12 wherein said correlator means  
2 comprises accumulator means for receiving said plurality of despread  
signals and for summing the despread signals over the length of the  
4 demodulation sequences.

14. The apparatus of Claim 12 wherein said received signal  
2 comprises a first received signal component and a second received signal  
component and wherein said demodulator means is for receiving said first  
4 received signal component and said second received signal component and  
for demodulating said first received signal component in accordance with a  
6 first plurality of demodulation sequences to provide a first plurality of  
despread signals and for demodulating said second received signal  
8 component in accordance with a second plurality of demodulation  
sequences to provide a second plurality of despread signals and wherein said  
10 sequence generator means is for generating said first plurality of  
demodulation sequences and said second plurality of demodulation  
12 sequences.

15. The apparatus of Claim 14 wherein said correlator means  
2 comprises:

first accumulator means for receiving said first plurality of despread  
4 signals and for summing each of said plurality of despread signals over the  
length of the demodulation sequences to provide a first plurality of despread  
6 sum values;

second accumulator means for receiving said second plurality of  
8 despread signals and for summing each of said plurality of despread signals  
over the length of the demodulation sequences to provide a second plurality  
10 of despread sum values;

combiner means for receiving said first plurality of despread sum  
12 values and for receiving said second plurality of despread sum values and  
for combining said first plurality of despread sum values and said second  
14 plurality of despread sum values to provide said signal correlation energy  
values.

16. The apparatus of Claim 15 wherein said combiner means  
2 comprises:

squaring means for receiving said first plurality of despread sum  
4 values and for receiving said second plurality of despread sum values and  
for squaring each of said first plurality of despread sum values and each of  
6 said second plurality of despread sum values and adding each of said first  
plurality of squared despread sum values to a corresponding one of said  
8 second plurality of squared despread sum values to provide a plurality of  
energy magnitude values; and

10 noncoherent combiner for receiving said plurality of energy  
magnitude values and computing said signal correlation energy values in  
12 accordance with said plurality of energy magnitude values.

17. The apparatus of Claim 16 wherein said searcher controller  
2 means is further for providing a combination signal and wherein said  
noncoherent combiner is responsive to said combination signal.

18. A system for selecting a synchronized demodulation sequence  
2 comprising:

a sequence generator having an input for receiving a first control  
4 signal and having an output;

a demodulator having an input coupled to said sequence generator  
6 output and having an output;

a correlator having an input coupled to said demodulator output and  
8 having an output; and

searcher controller having an input coupled to said correlator output.

19. The system of Claim 18 wherein said correlator is a coherent  
2 accumulator.

20. The system of Claim 18 wherein said sequence generator has a  
2 second output and wherein said demodulator has a second input coupled to  
said sequence generator second output.

21. The system of Claim 18 wherein said demodulator has a second  
2 output and wherein said correlator comprises:  
a first coherent accumulator having an input coupled to said  
4 demodulator output and having an output;  
a second coherent accumulator having an input coupled to said  
6 second demodulator output and having an output;  
a sum of the squares calculator having a first input coupled to said  
8 first coherent accumulator output and having a second input coupled to  
said second coherent accumulator output and having an output;  
10 a noncoherent accumulator having an input coupled to said sum of  
the squares calculator output.




FIG. 1






FIG. 2





FIG. 4



4/4




FIG. 5

## INTERNATIONAL SEARCH REPORT

Intern. Application No  
PC1/US 95/08659A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04B1/707

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04B H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,92 00639 (QUALCOMM, INC.) 9 January 1992 cited in the application see page 9, line 7 - line 25 see page 29, line 29 - page 30, line 6 see page 33, line 7 - line 17; figure 7 see page 43, line 17 - line 27 see page 50, line 9 - line 25; figure 9 ---	1,3-10, 12
X	US,A,5 177 765 (HOLLAND ET AL) 5 January 1993 see column 3, line 35 - line 39; claim 2 see column 4, line 5 - line 14 see column 8, line 26 - column 15, line 15; figures 3-8 -----	1,5-9, 12,18

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

10 November 1995

Date of mailing of the international search report

20. 11. 95

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bossen, M

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/08659

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9200639	09-01-92	US-A- 5103459	07-04-92
		AU-B- 652956	15-09-94
		AU-B- 8401691	23-01-92
		BG-A- 97222	27-05-94
		CN-A- 1061312	20-05-92
		EP-A- 0536334	14-04-93
		HU-A- 64657	28-01-94
		IL-A- 98598	27-02-94
		JP-T- 6501349	10-02-94
		US-A- 5416797	16-05-95
		US-A- 5309474	03-05-94
-----			
US-A-5177765	05-01-93	NONE	
-----			

**This Page Blank (uspto)**